


# Choosing at a Distance an Overall Distribution Exhibiting Either Which-Way Information or Interference Using a Single Optical Microcavity

Douglas M. Snyder  
 Los Angeles, California




Choosing at a distance either an overall distribution exhibiting ww information or instead no ww information is based on a delayed choice whether or not to keep the entanglement between paired photons where an idler photon provides which way information to a paired distant signal photon. The choice depends on either losing an idler photon passing through the apparatus in many other similar photons or not losing the idler photon. Initially both of the photons in a pair have ww info, but due to device setup the ww info for the signal particle is quickly lost. One example is Kim where the photon pairs are created at one of two "slits". Ww info is quickly lost for the signal photon since it travels a two slit setup after creation. Ww info is preserved for the idler photon since the two "slits" are followed by a prism that associates each "slit" with one of two widely separated paths. The result is the idler photon provides ww info to the distant entangled signal photon. If the idler photon is not lost in many other similar photons, the signal photons show an overall ww distribution. If the idler photon is lost before the signal photon is detected, the signal photons show a distribution exhibiting interference. Ultrafast switches for single entangled photons can be used to change the path/s for the idler photon while the idler photon is in flight so that an idler photon either is detected at one of two detectors on different idler photon paths (ww info) or instead enters an optical microcavity filled with photons similar to the idler photon and situated where two idler photon paths overlap (no ww info).

## Losing the Idler Photon and Its Which-Way Information

Allow that there is an entanglement where the entanglement depends on which-way information held by one photon I of two entangled photons S and I as in:  
 $\psi = 1/\sqrt{2} [(\psi_{S,A})|I_A\rangle + (\psi_{S,B})|I_B\rangle]$  where  $\langle I_A | I_B \rangle = 0$  and  $\langle I_B | I_A \rangle = 0$  where A and B refer to two slits, for example, one of which is where the photon pairs were initially entangled. In other words, the situation is where one entangled photon I provides which-way information to the other photon S. Then photon I and the which-way information carried by photon I is lost before any detections on either S or I are made. The result is that the entanglement between S and I is lost because the entanglement depends on the which way information that I supplies to S. Since the entanglement is lost, S shows an overall non which way distribution (interference) over a series of runs. If photon I and the which way information I carries are not lost before any detections on either S or I are made, the entanglement is maintained. Since the entanglement is maintained, I continues to provide which way information to S and S shows an overall which distribution over a series of runs. In one option in the experiment, entanglement is maintained. In the other option, entanglement which is based on one photon supplying which-way information to the other photon is lost. No correlations between S and I are needed to develop the which way or non which distributions of S.

Path length from photon sources to detector D3 > path length from photon sources to positions corresponding to the time the 2 HAK switches can be closed;  $t_{L1} < t_{L2}$

Switches in open position  
 All idler photons to D1 or D2



From creation of photon until detection:

$$\Psi_{total} = 1/\sqrt{2}(\psi_{S,A} \psi_{I,A} + \psi_{S,B} \psi_{I,B})$$

$$\langle \psi_{I,A} | \psi_{I,B} \rangle = 0$$

$$\langle \psi_{I,B} | \psi_{I,A} \rangle = 0$$

I - Idler  
 S - Signal

**P1**  
 For a pair of entangled signal idler photons, one may "lose" the idler photon that carries which-way information and provides which-way information to the entangled signal photon before the signal photon is detected, thereby losing the entanglement. Over a number of runs, the result is an overall non-ww distribution of the signal photons. If instead the idler photon is not lost, the idler photon continues to supply ww information to the signal photon and over a number of runs the result is an overall ww distribution of the signal photons. These different overall distributions of signal photons do not depend on correlating detections of the entangled paired signal photons. Not needing to correlate detections allows for a delayed choice on the idler photons to determine the distribution of distant signal photons (either overall ww or overall non ww) without having to make correlations between signal and idler photon detections.

**1. Introduction**  
 In quantum erasure (e.g., 1,2,3), fringes and anti-fringes occur and are developed through correlating measurements on both of two entangled particles (for example, atom-photon pairs in the Scully experiment and signal-idler photon pairs in the Kim experiment). [Figures 1 and 2 near here.] In addition, the fringes and anti-fringes resulting from quantum erasure sum to an overall which-way distribution pattern. One obtains an overall which-way distribution whether or not the overall distribution results from many experimental runs where there is quantum erasure or instead from many experimental runs where there is no quantum erasure (e.g., 1,3). The fringes and anti-fringes in quantum erasure indicate that specific which path information no longer exists with erasure, but as noted the only way to develop the fringes and anti-fringes in the quantum erasure is through correlating measurement results on the entangled paired particles.

In contrast, the proposed experiment allows for obtaining either distinct overall which-way or non-which-way distributions at a distance without correlating measurements on the two paired particles and using a delayed choice (4,5,6). The underlying method essentially involves setting up a situation where one of two entangled particles (particle A) supplies which-way information to the other (particle B). One then can make a delayed choice whether or not to lose the particle that supplies the which-way information to the other. Whether or not this particle is lost determines whether or not the entanglement is lost. If particle A is not lost over many runs, then particle B shows an overall which-way distribution. If particle A is lost over many runs, then particle B shows an overall non-which-way distribution (interference).

Figure 3 presents the method to obtain distinct overall which-way and non-which-way distributions at a distance. [Figure 3 near here.] The conceptual foundation of an experiment is developed below involving photons that implements the method in a practical way. A very important consequence of the experiment is that one can use delayed choice with the idler photons to determine the distribution of distant signal photons (overall ww or overall non ww distributions) without having to take time to make correlations between signal and idler photon measurements. The experiment provides the basis for a useful digital delayed choice quantum communications device.

**2. The Conceptual Foundation of the Experiment**  
 This section provides an outline of the conceptual foundation of the experiment, the first conceptual formulation of the experiment, and the conceptual formulation of a practical version of the experiment.

**2.1 Conceptual Outline of Experiment**  
 The proposed experiment relies on a delayed choice whether or not to keep the entanglement between paired signal and idler photons where the idler photon provides which-way information to a distant signal photon. One can produce an overall distribution of the signal photons showing interference by losing the idler photon in many other similar photons over many experimental runs or instead an overall which-way distribution for the signal photons at a distance by not losing their paired idler photons over many experimental runs. The idler photon is either detected or lost before the entangled signal photon is detected. Ultrafast switches for single entangled photons can be used to change the paths for the idler photon while the idler photon is in flight. An optical microcavity filled with photons similar to the idler photon can be used to lose the idler photon. No correlations between measurements on the paired signal-idler photons are needed to develop the signal photon distributions noted above.

**P2**  
 As a first test, movable mirrors can be used instead of the ultrafast switches to either send an idler photon to one of two detectors along the two idler photon paths or instead send the idler photon into an optical microcavity filled with photons similar to the idler photon. The result is two different distributions of the paired signal photons depending on whether or not the idler photons are lost before the paired signal photons are detected.

**2.2 The First Conceptual Formulation of the Experiment**  
 The first conceptual formulation of the experiment (6) employs the same setup as the quantum eraser experiment of Kim's quantum eraser setup (2) (Fig. 2) with certain changes.  
**2.2.1 The Kim Quantum Eraser** - The Kim quantum eraser uses a device that can act as an interferometer with two separate locations at the entrance where each of the locations has the possibility of generating an entangled signal idler photon pair but where only one location generates an entangled signal idler photon pair at a time. The two locations where the entangled signal idler photon pair can be generated are analogous to the two slits in a two-slit screen. The idler photons initially travel through the interferometer along one of two possible paths, each path associated with one of the two possible locations for generating an entangled signal idler photon pair. The signal photons travel away from the entrance of the interferometer and also from the paired idler photons in what for the signal photons are essentially a two slit device. The signal idler photon pair's entanglement incorporates the idler photon's providing which-way information to the signal photon that eventually manifests itself in the form of the overall distribution of the signal photons at their detection axis (one wide hump) in the quantum erasure condition in the Kim experiment.

Besides functioning as an interferometer that allowed for quantum erasure, Kim and his colleagues structured their device so that one-half of the idler photons passing through the first part of the device, specifically that part of the device from M to Y or Z, could instead provide definitive which-way information regarding the specific paths of paired signal photons when correlations between detection events for paired signal and idler photons are made. They accomplished this through the use of beam splitters instead of full-silvered mirrors at Y and Z. In their experiment, 1/2 of the generated idler photons traveled through the beam splitters at Y and Z instead of being reflected at Y and Z toward beam splitter BS at N.

Our concern here, though, is with the 1/2 of the idler photons that are reflected off the beam splitters at Y or Z. For the 1/2 of the generated idler photons that are instead reflected at the beam splitters at Y or Z toward BS at N and that are subsequently detected at either detector D1 or detector D2, the distributions of the signal photons detected at D3 along a spatial axis x correlated with the detections of their paired idler photons are two multiple narrow hump sub-distributions that indicate the presence of interference (i.e., fringes and anti-fringes).

As noted, the fringes and anti-fringes sub-distributions for the signal photons sum to the one wide hump characteristic of which-way information. These fringes and anti-fringes indicate the loss of which-way information concerning the specific path through the interferometer of the paired idler photons that are reflected from BS at N. This specific which-way information concerning the path of the idler photon through the interferometer until BS at N stemmed from the origin of the entangled idler and signal photon pairs at one specific location of two possible ones at which the signal-idler photon pair could be generated.

Even though specific which-way information is lost concerning the path of the idler photon through the interferometer when the idler photon passes through BS at N, general which-way information appears to be preserved (since the entanglement is preserved) in the overall one wide hump distribution of the signal photons of the signal-idler photon pairs. An inspection of Figure 2 shows that when the idler photon passes through BS at N, it has arrived via a single path since it originated at I of the two "slits". This general which-way information that the idler photon arrived at BS at N from one of two possible paths is preserved in the overall which-way distribution of the idler photons. This overall which-way distribution is the sum of the fringes and anti-fringes where these fringes and anti-fringes depend on correlations between paired signal and idler photons and where these fringes and anti-fringes show the loss of specific which-way information concerning at which "slit" of the two possible "slits" the signal idler photon pair was created even though we know that the signal-idler pair was created at one of them.

Fig. 3

**ENTANGLEMENT BETWEEN PARTICLES 1 AND 2 WHERE ENTANGLEMENT OCCURS AT ONE OF TWO POSSIBLE LOCATIONS (PROVIDING WHICH WAY INFORMATION).**

**ENTANGLED PARTICLES PHYSICALLY SEPARATE FROM EACH OTHER WHERE ONE PARTICLE [P1] PRESERVES WW INFORMATION THAT ACCOMPANIED ENTANGLEMENT AND THE OTHER PARTICLE'S MOTION [P2] SUPPORTS INTERFERENCE IN P2'S OVERALL DISTRIBUTION DUE TO DEVICE SETUP.**

**With this step, Particle 1 now supplies which-way information to Particle 2 due to the entanglement.**

**DELAYED CHOICE AT A DISTANCE**

**CHOICE A**  
**ESSENTIALLY LOSE P1 (AND THE WW INFORMATION IT CARRIES) IN MANY OTHER PARTICLES OF SIMILAR CHARACTER TO P1 BEFORE P2 IS DETECTED AND BEFORE WW INFO BECOMES AVAILABLE TO THE ENVIRONMENT OR AN IRREVERSIBLE WW MEASUREMENT IS MADE ON P1. (THE ENTANGLEMENT IS THEN LOST AND SO IS THE WW INFORMATION SUPPLIED BY P1 TO P2.)**

**Repeat runs with choice A 100 times consecutively to develop overall interference distribution pattern for P2.**


**CHOICE B**  
**DO NOT LOSE P1 THAT CARRIES WW INFORMATION. (THE ENTANGLEMENT IS NOT LOST AND NEITHER IS THE WW INFORMATION P1 HAS SUPPLIED TO P2.)**

**Repeat runs with choice B 100 times consecutively to develop overall ww distribution pattern for P2.**

Path length from photon sources to detector D3 > path length from photon sources to positions corresponding to the time the 2 HAK switches can be closed;  $t_{L1} < t_{L2}$

Switches in closed position at  $t_c$ . All idler photons lost in OMC's

Time  $t_c$  when the 2 switches closed  
 0 idler photons are detected at D1



From creation of photon until time  $t_{L1}$ :

$$\Psi_{total} = 1/\sqrt{2}(\psi_{S,A} \psi_{I,A} + \psi_{S,B} \psi_{I,B})$$

$$\langle \psi_{I,A} | \psi_{I,B} \rangle = 0$$

$$\langle \psi_{I,B} | \psi_{I,A} \rangle = 0$$

I - Idler  
 S - Signal

**P3**  
 As noted, which-way information regarding the distribution of the signal photon at its detection axis is not provided in the Kim experiment by the signal photon itself traveling away from the interferometer and toward the spatial axis where its location is detected. Shortly after the signal-idler photon pair is generated, due to the dimensions of the "double slit," the component wave functions for the signal photon for the two possible locations where the signal-idler photon pair were created (i.e., the "double slit") overlap.  
 The dimensions of the double slit relative to the wavelength of the signal photons supports interference in the distribution of the signal photons at their detection axis in the absence of which-way information provided by the paired idler photons.

**2.2.2 Alterations in the Kim Quantum Eraser and Their Implications in the First Conceptual Formulation of the Experiment** - The following changes are made in the Kim quantum eraser: [Figures 4 and 5 near here.]  
 1. Only the first two arms of the interferometer over which the idler photons can travel, with each arm starting at one of the two possible photon sources, are used.  
 2. At the end of each of these arms is a photon detector instead of a beam splitter.  
 3. The portion of the apparatus through which the idler photon travels is isolated from the environment until just before the photon detectors. The portion of the apparatus through which the signal photon travels is also isolated until just before the signal photon is detected.  
 4. Attached to the container through which the idler photon travels are two reservoirs containing many photons similar in character to the idler photon. These reservoirs are closed off from the container but can be opened so that the photons in the reservoirs are injected into the container.

In the present experiment, the idler photon can be essentially lost before the signal photon is detected and before which-way information from the idler photon is available to the environment. In other words, we begin with Eqn. 1 below, but with the essential loss of the idler photon as noted. Eqn. 2 that describes only the signal photon since the entanglement is lost since the idler photon is lost.

$$\psi = 1/\sqrt{2}[(S_A)|I_A\rangle + (S_B)|I_B\rangle] \quad [1]$$

where S and I represent the signal and idler photons, respectively, and A and B represent the two possible locations where the signal-idler photons are initially created. Eqn. 1 is the equation for the quantum eraser (1), and it is known to be correct because of the empirical evidence that supports the quantum eraser (e.g., 1,2,3). As noted, we rely on the first part of the Kim quantum eraser setup in which the entangled signal idler photon pairs are generated and therefore Eqn. 1 is applicable in the proposed experiment until the idler photon is lost and the signal idler photon entanglement is lost.

$$\psi = [1/\sqrt{2}[(S_A) + (S_B)]] \quad [2]$$

$$|\psi|^2 = 1/2 [(S_A)^2 + (S_A)^*(S_B) + (S_B)^*(S_A) + (S_B)^2] \quad [3]$$

Eqn. 2 is not the quantum eraser because in the quantum eraser entanglement is maintained (e.g., 1,2,3).  
 Essentially, the Kim setup is altered through introducing the possibility of "losing" the entangled idler photon in many similar photons before the paired signal photon is detected. In the first conceptual formulation, these photons similar to the idler photon are injected into a container through which the idler photon is traveling before the idler photon reaches a detector and that isolates the idler photon from the environment. At the creation of the entangled signal-idler photon pairs, both the signal and idler photons possess which-way information due to their creation at one of two "slits". After their creation, the signal photon immediately loses its which-way information since the signal photon is essentially in a two slit device setup and pathways to the signal photon detector overlap. On the other hand, the idler photon maintains the which-way information since each "slit" leads to a separate path in the first part of an interferometer. Over a series of runs, if the idler photon is lost in many other similar photons, the signal photon, having no which-way information of its own, shows an overall distribution of non-which-way information, an interference pattern (Eqn. 3). If the idler photon is not lost, over a series of runs the signal photon shows an overall which-way distribution pattern (the absolute square of Eqn. 1 which is Eqn. 5 below). The distribution of the signal photons in this case given by

$$P4 \quad |\psi|^2 = 1/2 [(S_A)^2 + (S_A)^*(S_B) + (S_B)^*(S_A) + (S_B)^2] \quad [4]$$

$$\langle (S_A^* S_B) | \langle (L_A | L_B) \rangle + \langle (S_B^* S_A) | \langle (L_B | L_A) \rangle \rangle \quad [5]$$

where  $\langle L_A | L_B \rangle$  and  $\langle L_B | L_A \rangle$  then serve as which-way markers or  $\langle \psi_{I,A} | \psi_{I,B} \rangle = 1/2(S_A)^2 + 1/2(S_B)^2$  since

$$\langle L_A | L_B \rangle = 0 \quad [6]$$

$$\langle L_B | L_A \rangle = 0 \quad [7]$$

**2.3 A Practical Conceptual Formulation of the Experiment**  
 The first conceptual formulation of the experiment appeared difficult to implement so two questions were investigated: 1) would it be possible to switch the idler photon from paths leading to detectors to paths that would lead the idler photon to a mechanism where the idler photon would be lost in many similar photons? 2) does such a mechanism exist where the idler photon could be lost in many similar photons? [Figures 6 and 7 near here.]

Regarding point 1, an ultrafast switch for a single entangled photon developed by Hall, Altepeter, and Kumar (HAK) (7,8) was found that would switch the idler photon from paths leading to detectors to paths that would lead the idler photon to a mechanism where the idler photon would be lost in many similar photons. Regarding point 2, an optical microcavity filled with many photons similar to the idler photon is a device in which the idler photon could be lost in many similar photons (9). (Jan Wiersig confirmed in a personal communication that a small microcavity with a high quality factor would work. Possible candidates are microdisks, micropillars, and photonic crystal defect cavities.) The optical microcavity is situated at the crossing point for the two idler photon paths that occur when the ultrafast switches located on the two possible paths for the photon after it is created are on, (Wiersig confirmed that a single optical microcavity would work in the setup 1) figures. Figures 6 and 7 present the practical conceptual formulation of the experiment. With these new features, the reservoirs of photons similar to the idler photon are not needed and are removed in this practical conceptual formulation of the experiment. Other features of the first conceptual formulation of the experiment are not changed.

To begin with, one might substitute movable mirrors for the HAK switches that could be moved between one position that directs the idler photons to photon detectors over a number of experimental runs and another position that directs the idler photons to an optical microcavity filled with photons similar to the idler photon over a number of experimental runs.  
**3. A Digital Quantum Communications Device**  
 The conceptual formulation of the experiment allows for distinct which-way and non-which-way distributions of the signal photons depending on whether paired idler photons with which the signal photons are entangled are lost. As noted, no correlations are needed between the signal photon measurements and the idler photon measurements to develop either the which-way or instead non-which-way distributions of the paired signal photons with which the idler photons are entangled. A very important consequence is that one can use delayed choice with the idler photons to determine the distribution of distant signal photons (overall ww or overall non ww distributions) without having to take time to make correlations between signal and idler photon measurements. The experiment provides the basis for a useful digital delayed choice quantum communications device. The which-way and non-which-way distributions can represent two bits 0 and 1, respectively. This possibility indicates that the conceptual formulation of the experiment could lead to the development of a useful digital delayed choice quantum communications device.

**4. Conclusion**  
 The conceptual foundation for a practical experiment to obtain overall distinct which-way and non-which-way distributions at a distance using a delayed choice and without needing to correlate measurements on paired particles has been presented. The conceptual formulation of the proposed experiment differs from the quantum eraser in at least one important way, namely the fringes and anti-fringes of the quantum eraser depend on correlating measurement events on the members of entangled paired particles and the conceptual formulation of the proposed experiment does not. The experimental setup used by Kim is changed to allow for a delayed choice of: 1) losing the idler photon in many similar photons before the paired signal photon is detected and before which-way information on the idler photon is available in the environment, or 2) not losing the idler photon which is then detected at one of two idler photon detectors. Ultrafast switches are used to route the idler photon either toward the photon detectors or toward an optical microcavity where the idler photon is lost in many similar photons. Losing the idler photon means losing the entanglement between paired signal and idler photons. The different distributions of the signal photons can be used as the basis for a useful digital delayed choice quantum communications device.

**5. References**  
 1. Scully, M., Englert, B. and Walther H. 1991. *Nature*, 351: 111-116  
 2. Kim, Y., Yu, R., Kulik, S.P., Shih, Y. and Scully, M. 2000. *Phys. Rev. Lett.* 84: 1-5.  
 3. Walborn, S.P., Terra Cunha, M.O., Padua, S., and Monken, C.H. 2002. *Phys. Rev. A*, 65: 033818-1 to 033818-6.  
 4. Wheeler, J. 1978. "The Past and the 'Delayed-Choice' Double-Slit Experiment," in *Mathematical Foundations of Quantum Theory*, pp. 9-48, [A. Marlow, Ed], Academic Press.  
 5. Wheeler, J. 1984. "Law Without Law," in *Quantum Theory and Measurement*, pp. 182-213, J. Wheeler and W. Zurek, Eds., Princeton University Press.  
 6. Snyder, D.M. 2012. *Bull. Am. Phys. Soc.*, 57. [http://meeting.aps.org/journals/BAPS/2012/MAR/K1\\_301](http://meeting.aps.org/journals/BAPS/2012/MAR/K1_301).  
 7. Hall, M.A., Altepeter, J.B. and Kumar, P. 2011. *Phys. Rev. Lett.* 106: 053901. [dx.doi.org/10.1103/PhysRevLett.106.053901](http://dx.doi.org/10.1103/PhysRevLett.106.053901) [quant-ph].  
 8. Hall, M.A., Altepeter, J.B. and Kumar, P. 2011. *New Journal of Physics* 13: 103004.  
 9. Vihala, K.J. 2003. *Nature*, 424: 839-846.